



328300




328160




328220



328260



328300



328330




328350




328370



328390



328650



328850

328000 / T328000

## COM 1000

– quality and functionality for all times

COM 1000, with its stringently simple design, embodies a timeless carpet where high quality plays the leading role alongside functionality beyond the ordinary. The classic expression carries reminders of cobblestone paving, which has had significant architectural importance over time with its patterned surfaces in urban spaces. Available both as broadloom, square carpet tiles, ZigZag-Tiles<sup>®</sup>, and as LockTiles<sup>®</sup>.

Available in 10 timeless colours. Felt backing from +200 m<sup>2</sup>.

# COM 1000

## 328000 / T328000




### Technical data

	Standard	Broadloom w/Textile	Broadloom w/Felt	Tiles
Type of manufacture	ISO 2424	Woven	Woven	Woven
Structure	ISO 2424	Loop pile	Loop pile	Loop pile
Pile material	ISO 2424	100% PA 6.0	100% PA 6.0	100% PA 6.0
Dye method		Solution dyed	Solution dyed	Solution dyed
Primary backing	ISO 2424	PES	PES	PES
Secondary backing	ISO 2424	rPET Textile	rPET Felt	TEXtiles®
Dimensions/Width	ISO 3018	Approx. 400 cm	Approx. 400 cm	50 x 50 cm (5 m <sup>2</sup> /box)
Surface pile thickness	ISO 1766	Approx. 2.00 mm	Approx. 2.00 mm	Approx. 2.00 mm
Total thickness	ISO 1765	Approx. 3.00 mm	Approx 4.00 mm	Approx. 4.5 mm
Total pile mass	ISO 2424	Approx. 400 g/m <sup>2</sup>	Approx. 400 g/m <sup>2</sup>	Approx. 400 g/m <sup>2</sup>
Total mass	ISO 8543	Approx. 1,750 g/m <sup>2</sup>	Approx. 2,100 g/m <sup>2</sup>	Approx. 3,100 g/m <sup>2</sup>
Stitch rate	ISO 1763	Approx. 164,000 /m <sup>2</sup>	Approx. 164,000 /m <sup>2</sup>	Approx. 164,000 /m <sup>2</sup>
Antistatic	ISO 6356	≤ 2 kV	≤ 2 kV	≤ 2 kV
Classification for use	EN 1307	23 Domestic - Intensive use	23 Domestic - Intensive use	23 Domestic - Intensive use
Classification for use	EN 1307	33 Commercial - Heavy	33 Commercial - Heavy	33 Commercial - Heavy
Luxury rating class	EN 1307	LC1	LC1	LC1
Dimensional stability	EN 986	-	-	≤ 2,0 %
Castor chair suitability	EN 985	Intensive use	Intensive use	Intensive use
Impact sound reduction	ISO 10140	Approx. ΔL <sub>w</sub> 14 dB	Approx. ΔL <sub>w</sub> 18 dB	Approx. ΔL <sub>w</sub> 20 dB
Sound absorption	EN ISO 354	Approx. 0.10 α <sub>w</sub>	Approx. 0.15 α <sub>w</sub>	Approx. 0.20 α <sub>w</sub>
Thermal resistance	ISO 8302	Approx. 0.06 m <sup>2</sup> K/W	Approx. 0.09 m <sup>2</sup> K/W	Approx. 0.10 m <sup>2</sup> K/W
Fireclass	EN 13501-1	C <sub>fl</sub> - s1	C <sub>fl</sub> - s1	B <sub>fl</sub> - s1


### Recommended tile installation




LockTiles®



ZigZag-Tiles®



Square






# COM 1000

## 328000 / T328000



### Certifications

	Standard	 Broadloom w/Textile	 Broadloom w/Felt	 Tiles
CE	EN 14041	0809-CPR-19006044-C3	0809-CPR-19006044-C3	0809-CPR-19006044-C7
DOP	EN 14041	1118#19006044-C3	1118#19006044-C3	1118#19006044-C7
UKCA	EN 14041	0086 CPR 780063	0086 CPR 780063	0086 CPR 780067
IACG	EN 16516	Compliant	Compliant	Compliant
M1		Compliant	Compliant	Compliant
GUI		Compliant	Compliant	Compliant
GUT		Compliant	Compliant	Compliant
EPD - GWP A1-A3	ISO 14025 EN 15804+A2	8.13 kg CO <sub>2</sub> - Eq	8.13 kg CO <sub>2</sub> - Eq	8.85 kg CO <sub>2</sub> - Eq
PEF - LCA Scope 3 CO <sub>2</sub> - Eq according to EU PEF Standard		8.7 kg CO <sub>2</sub> - Eq	9.2 kg CO <sub>2</sub> - Eq	10.7-11.0 kg CO <sub>2</sub> - Eq
Reach		Compliant	Compliant	Compliant
BREEAM NOR		Compliant	Compliant	Compliant
Recycled content		100% recycled backing	100% recycled backing	100% recycled backing



As we continuously improve our products and testing procedures, any above declaration is subject to amendments without prior notice.  
For the latest technical specifications, installation and maintenance guide visit:

[www.fletcocarpets.com](http://www.fletcocarpets.com)