


371350



371150




371210




371220



371260



371280




371330




371350




371380



371600



371650



371680




371740



371800




371850



371870



371880



371390



371480

371000 / T371000

















Zenith

– soft as the green forest floor

Zenith is as soft as moss on the forest floor and boasts exceptionally good sound-absorbing properties. With its tufted and cut pile, the carpet brings the deep, serene tranquility of the forest – the joy of nature and peace celebrated in an old Danish folk song, which is so sought after in modern life. Available as broadloom and as square carpet tiles in a plethora of dynamic colours, creating an exclusive expression.

Available in 18 vibrant colours. Special colours from +200 m². Felt backing from +200 m².


Technical data

| | Standard |  Broadloom w/Textile |  Broadloom w/Felt |  Tiles |
|--|------------|--|---|---|
| Type of manufacture | ISO 2424 | Tufted 1/10 | Tufted 1/10 | Tufted 1/10 |
| Structure | ISO 2424 | Cut pile | Cut pile | Cut pile |
| Pile material | ISO 2424 | 100% PA 6.6 | 100% PA 6.6 | 100% PA 6.6 |
| Dye method | | Continuos dyed | Continuos dyed | Continuos dyed |
| Primary backing | ISO 2424 | PES non woven | PES non woven | PES non woven |
| Secondary backing | ISO 2424 | rPET Textile | rPET Felt | TEXtiles® |
|  Dimensions/Width | ISO 3018 | Approx. 400 cm | Approx. 400 cm | 50 x 50 cm (5 m ² /box) |
| Surface pile thickness | ISO 1766 | Approx. 3.50 mm | Approx. 3.50 mm | Approx. 3.50 mm |
|  Total thickness | ISO 1765 | Approx. 6.50 mm | Approx 7.50 mm | Approx. 8.00 mm |
| Total pile mass | ISO 2424 | Approx. 1,000 g/m ² | Approx. 1,000 g/m ² | Approx. 1,000 g/m ² |
|  Total mass | ISO 8543 | Approx. 2,400 g/m ² | Approx. 2,850 g/m ² | Approx. 3,300 g/m ² |
| Stitch rate | ISO 1763 | Approx. 200,000 /m ² | Approx. 200,000 /m ² | Approx. 200,000 /m ² |
|  Antistatic | ISO 6356 | ≤ 2 kV | ≤ 2 kV | ≤ 2 kV |
|  Classification for use | EN 1307 | 23 Domestic - Intensive use | 23 Domestic - Intensive use | 23 Domestic - Intensive use |
|  Classification for use | EN 1307 | 33 Commercial - Heavy | 33 Commercial - Heavy | 33 Commercial - Heavy |
|  Luxury rating class | EN 1307 | LC3 | LC3 | LC3 |
|  Dimensional stability | EN 986 | - | - | ≤ 2,0 % |
|  Castor chair suitability | EN 985 | Intensive use | Intensive use | Intensive use |
|  Impact sound reduction | ISO 10140 | Approx. ΔL _w 26 dB | Approx. ΔL _w 30 dB | Approx. ΔL _w 27 dB |
|  Sound absorption | EN ISO 354 | Approx. 0.14 α _w | Approx. 0.16 α _w | Approx. 0.20 α _w |
|  Thermal resistance | ISO 8302 | Approx. 0.06 m ² K/W | Approx. 0.09 m ² K/W | Approx. 0.07 m ² K/W |
|  Fireclass | EN 13501-1 | C _{fl} - s1 | C _{fl} - s1 | B _{fl} - s1 |


Recommended tile installation




LockTiles®






ZigZag-Tiles®



Square



Certifications

| | Standard |  Broadloom w/Textile |  Broadloom w/Felt |  Tiles |
|--|----------|--|---|---|
| CE | EN 14041 | 0809-CPR-19006044-C3 | 0809-CPR-19006044-C3 | 0809-CPR-19006044-C7 |
| DOP | EN 14041 | 1118#19006044-C3 | 1118#19006044-C3 | 1118#19006044-C7 |
| UKCA | EN 14041 | 0086 CPR 780063 | 0086 CPR 780063 | 0086 CPR 780067 |
| IACG | EN 16516 | Compliant | Compliant | Compliant |
| M1 | | Compliant | Compliant | Compliant |
| PEF - LCA Scope 3 CO ₂ - Eq according to EU PEF Standard | | 12.0 kg CO ₂ - Eq | 12.0 kg CO ₂ - Eq | 14.0 kg CO ₂ - Eq |
| Reach | | Compliant | Compliant | Compliant |
| BREEAM NOR | | Compliant | Compliant | Compliant |
| Recycled content | | 100% recycled backing | 100% recycled backing | 100% recycled backing |



As we continuously improve our products and testing procedures, any above declaration is subject to amendments without prior notice.
For the latest technical specifications, installation and maintenance guide visit:

www.fletcocarpets.com