


T467450



T467250




T467350




T467360




T467370




T467390



T467450



T467650



T467750



T467850

T467000

## Stellar

















– the new star on the floor

A new star in the world of flat-woven carpets has emerged from our ongoing product development in weaving. Here, the master weaver has created a unique structure that captures the depth of space, where stars and other celestial bodies emerge against a dark background of infinity and eternity.

Available both as square carpet tiles, ZigZag-Tiles<sup>®</sup>, and as LockTiles. Stellar LockTiles<sup>®</sup> have won the prestigious iF DESIGN AWARD 2024.

Available in nine well-balanced colours. Special colours from +200 m<sup>2</sup>.


### Technical data

	Standard	 Broadloom w/Textile	 Broadloom w/Felt	 Tiles
Type of manufacture	ISO 2424			Woven
Structure	ISO 2424			Loop pile
Pile material	ISO 2424			100% PA 6.0 Econyl®
Dye method				Continuous dyed
Primary backing	ISO 2424			PES
Secondary backing	ISO 2424			TEXtiles®
 Dimensions/Width	ISO 3018			50 x 50 cm (5 m <sup>2</sup> /box)
Surface pile thickness	ISO 1766			Approx. 2.80 mm
 Total thickness	ISO 1765			Approx. 5.00 mm
Total pile mass	ISO 2424			Approx. 575 g/m <sup>2</sup>
 Total mass	ISO 8543			Approx. 3,320 g/m <sup>2</sup>
Stitch rate	ISO 1763			Approx. 204,000 /m <sup>2</sup>
 Antistatic	ISO 6356			≤ 2 kV
 Classification for use	EN 1307			23 Domestic - Intensive use
 Classification for use	EN 1307			33 Commercial - Heavy
 Luxury rating class	EN 1307			LC1
 Dimensional stability	EN 986			≤ 0.2 %
 Castor chair suitability	EN 985			Intensive use
 Impact sound reduction	ISO 10140			Approx. ΔL <sub>w</sub> 20 dB
 Sound absorption	EN ISO 354			Approx. 0.20 a <sub>w</sub>
 Thermal resistance	ISO 8302			Approx. 0.10 m <sup>2</sup> K/W
 Fireclass	EN 13501-1			B <sub>fl</sub> - s1


### Recommended tile installation




LockTiles®






ZigZag-Tiles®



Square



### Certifications

	Standard	 Broadloom w/Textile	 Broadloom w/Felt	 Tiles
CE	EN 14041			0809-CPR-19006044-C7
DOP	EN 14041			1118#19006044-C7
IACG	EN 16516			Compliant
GUI				Compliant
GUT				Compliant
PEF - LCA Scope 3 CO <sub>2</sub> - Eq according to EU PEF Standard				10.7-11.0 kg CO <sub>2</sub> - Eq
Reach				Compliant
BREEAM NOR				Compliant
Recycled content				100% recycled backing



As we continuously improve our products and testing procedures, any above declaration is subject to amendments without prior notice.  
For the latest technical specifications, installation and maintenance guide visit:

[www.fletcocarpets.com](http://www.fletcocarpets.com)