




371350



371150



371210



371220




371260




371280




371330




371350




371380




371600




371650



371680




371740




371800




371850



371870



371880



371390



371480

371000 / T371000




Zenith

– soft as the green forest floor

Zenith is as soft as moss on the forest floor and boasts exceptionally good sound-absorbing properties. With its tufted and cut pile, the carpet brings the deep, serene tranquility of the forest – the joy of nature and peace celebrated in an old Danish folk song, which is so sought after in modern life. Available as broadloom and as square carpet tiles in a plethora of dynamic colours, creating an exclusive expression.

Available in 18 vibrant colours. Special colours from +200 m². Felt backing from +200 m².


Technical data

	Standard	 Broadloom w/Textile	 Broadloom w/Felt	 Tiles
Type of manufacture	ISO 2424	Tufted 1/10	Tufted 1/10	Tufted 1/10
Structure	ISO 2424	Cut pile	Cut pile	Cut pile
Pile material	ISO 2424	100% PA 6.6	100% PA 6.6	100% PA 6.6
Dye method		Continuos dyed	Continuos dyed	Continuos dyed
Primary backing	ISO 2424	PES non woven	PES non woven	PES non woven
Secondary backing	ISO 2424	rPET Textile	rPET Felt	TEXtiles®
 Dimensions/Width	ISO 3018	Approx. 400 cm	Approx. 400 cm	50 x 50 cm (5 m ² /box)
Surface pile thickness	ISO 1766	Approx. 3.50 mm	Approx. 3.50 mm	Approx. 3.50 mm
 Total thickness	ISO 1765	Approx. 6.50 mm	Approx 7.50 mm	Approx. 8.00 mm
Total pile mass	ISO 2424	Approx. 1.000 g/m ²	Approx. 1.000 g/m ²	Approx. 1.000 g/m ²
 Total mass	ISO 8543	Approx. 2,400 g/m ²	Approx. 2,850 g/m ²	Approx. 3,300 g/m ²
Stitch rate	ISO 1763	Approx. 200,000 /m ²	Approx. 200,000 /m ²	Approx. 200,000 /m ²
 Antistatic	ISO 6356	≤ 2 kV	≤ 2 kV	≤ 2 kV
 Classification for use	EN 1307	23 Domestic - Intensive use	23 Domestic - Intensive use	23 Domestic - Intensive use
 Classification for use	EN 1307	33 Commercial - Heavy	33 Commercial - Heavy	33 Commercial - Heavy
 Luxury rating class	EN 1307	LC3	LC3	LC3
 Dimensional stability	EN 986	-	-	≤ 0.2 %
 Castor chair suitability	EN 985	Intensive use	Intensive use	Intensive use
 Impact sound reduction	ISO 10140	Approx. ΔL _w 26 dB	Approx. ΔL _w 30 dB	Approx. ΔL _w 27 dB
 Sound absorption	EN ISO 354	Approx. 0.14 α _w	Approx. 0.16 α _w	Approx. 0.20 α _w
 Thermal resistance	ISO 8302	Approx. 0.06 m ² K/W	Approx. 0.09 m ² K/W	Approx. 0.07 m ² K/W
 Fireclass	EN 13501-1	C _{fl} - s1	C _{fl} - s1	B _{fl} - s1


Recommended tile installation




LockTiles®






ZigZag-Tiles®



Square



Certifications

	Standard	 Broadloom w/Textile	 Broadloom w/Felt	 Tiles
CE	EN 14041	0809-CPR-19006044-C3	0809-CPR-19006044-C3	0809-CPR-19006044-C7
DOP	EN 14041	1118#19006044-C3	1118#19006044-C3	1118#19006044-C7
UKCA	EN 14041	0086 CPR 780063	0086 CPR 780063	0086 CPR 780067
IACG	EN 16516	Compliant	Compliant	Compliant
M1		Compliant	Compliant	Compliant
PEF - LCA Scope 3 CO ₂ - Eq according to EU PEF Standard		12.0 kg CO ₂ - Eq	12.0 kg CO ₂ - Eq	14.0 kg CO ₂ - Eq
Reach		Compliant	Compliant	Compliant
BREEAM NOR		Compliant	Compliant	Compliant
Recycled content		100% recycled backing	100% recycled backing	100% recycled backing



As we continuously improve our products and testing procedures, any above declaration is subject to amendments without prior notice.
For the latest technical specifications, installation and maintenance guide visit:

www.fletcocarpets.com